

Safety data sheet Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 1 / 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name
Isobutane

EC No (from EINECS): 200-857-2
CAS No: 75-28-5
Index-Nr. 601-004-00-0
Chemical formula C₄H₁₀
REACH Registration number:
Not available.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial and professional. Perform risk assessment prior to use.

Uses advised against

Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification

BOC, Priestley Road, Worsley, Manchester M28 2UT
E-Mail Address ReachSDS@boc.com

1.4. Emergency telephone number

Emergency phone numbers (24h): 0800 111 333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification acc. to Regulation (EC) No 1272/2008/EC (CLP/GHS)

Press. Gas (Liquefied gas) - Contains gas under pressure; may explode if heated.
Flam. Gas 1 - Extremely flammable gas.

Classification acc. to Directive 67/548/EEC & 1999/45/EC

F+; R12
Extremely flammable.

Risk advice to man and the environment

Liquefied gas.
Contact with liquid may cause cold burns/frost bite.

2.2. Label elements

- Labelling Pictograms



- Signal word

Danger

- Hazard Statements

H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.

- Precautionary Statements

Precautionary Statement Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautionary Statement Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.

Precautionary Statement Storage

P403 Store in a well-ventilated place.

Precautionary Statement Disposal

None.

2.3. Other hazards

Contact with liquid may cause cold burns/frost bite.

SECTION 3: Composition/information on ingredients

Substance / Mixture: Substance.

3.1. Substances

Isobutane
CAS No: 75-28-5
Index-Nr.: 601-004-00-0
EC No (from EINECS): 200-857-2
REACH Registration number:
Not available.

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

First Aid General Information:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First Aid Inhalation:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First Aid Skin / Eye:

For liquid spillage - flush with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance. Immediately flush eyes thoroughly with water for at least 15 minutes.

First Aid Ingestion:

Ingestion is not considered a potential route of exposure.

Safety data sheet Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 2 / 6

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Irregular cardiac activity.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Fire fighting measures

5.1. Extinguishing media

Suitable extinguishing media

All known extinguishants can be used.

Unsuitable extinguishing media

Do not use a solid water stream.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products

If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition:

Carbon monoxide, Carbon dioxide.

5.3. Advice for fire-fighters

Specific methods

If possible, stop flow of product. Move container away or cool with water from a protected position. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Prevent water used in emergency cases from entering sewers and drainage systems.

Special protective equipment for fire-fighters

Use self-contained breathing apparatus and chemically protective clothing. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to EN 469 will provide a basic level of protection from chemical incidents. EN 469:2005: Protective clothing for fire-fighters. Performance requirements for protective clothing for fire-fighting.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use self-contained breathing apparatus and chemically protective clothing. Evacuate area. Ensure adequate air ventilation. Eliminate ignition sources. Consider the risk of potentially explosive atmospheres. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Only experienced and properly instructed persons should handle gases under pressure. The substance must be handled in accordance with good industrial hygiene and safety procedures. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Purge air from system before introducing gas. Keep away from ignition sources (including static discharges). Do not smoke while handling product. Assess the risk of potentially explosive atmosphere and the need for explosion-proof equipment. Consider the use of only non-sparking tools. Ensure the complete gas system has been (or is regularly) checked for leaks before use. Refer to supplier's handling instructions. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

7.2. Conditions for safe storage, including any incompatibilities

Secure cylinders to prevent them from falling. Segregate from oxidant gases and other oxidants in store. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. Containers should be stored in the vertical position and properly secured to prevent falling over. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. All electrical equipment in the storage areas should be compatible with the risk of potentially explosive atmosphere. Containers should not be stored in conditions likely to encourage corrosion.

Safety data sheet Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 3 / 6

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Value type	value	Note
TLV - TWA	800ppm	

DNEL not available
PNEC not available

8.2. Exposure controls

Appropriate engineering controls

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep concentrations well below occupational exposure limits. Gas detectors should be used when quantities of flammable gases/vapours may be released. Consider work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages. Provide adequate general or local ventilation. The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

Personal protective equipment

Protect eyes, face and skin from liquid splashes. Wear a face-shield when transfilling and breaking transfer connections. Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Full-face mask recommended.

Guideline:

EN 136: Respiratory protective devices. Full face masks. Requirements, testing, marking.

Skin protection

Hand protection

Advice:

Wear cold insulating gloves.

Guideline:

EN 511 Protective gloves against cold.

Advice: Wear working gloves and safety shoes while handling gas cylinders.

Body protection

Protect eyes, face and skin from contact with product. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Guideline:

EN 943: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles.

Other protection

Wear flame resistant/retardant clothing. Take precautionary measures against static discharges. Wear working gloves and safety shoes while handling gas cylinders. ISO 20345 Safety footwear.

Respiratory protection

Keep self contained breathing apparatus readily available for emergency use. Use SCBA in the event of high concentrations. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used.

Guideline:

EN 136: Respiratory protective devices. Full face masks. Requirements, testing, marking.

Material:

Filter AX

Guideline:

EN 14387: Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking

Thermal hazards

If there is a risk of contact with the liquid, all protective equipment should be suitable for extremely low temperatures.

Environmental Exposure Controls

Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General information

Appearance/Colour: Colourless gas.

Odour: Sweetish. Poor warning properties at low concentrations. Stenchant often added

Odour threshold:

Odour threshold is subjective and inadequate to warn for over exposure.

Melting point: -159 °C

Boiling point: -12 °C

Flash point: Not applicable for gases and gas mixtures.

Evaporation rate:

Not applicable for gases and gas mixtures.

Flammability range: 1,5 %(V) - 9,4 %(V)

Vapour Pressure 20 °C: 3 bar

Relative density, gas: 2

Solubility in water: 54 mg/l

Partition coefficient: n-octanol/water: 2,76 logPow

Autoignition temperature: 460 °C

Explosive properties:

Explosive acc. EU legislation: Not explosive.

Explosive acc. transp. reg.: Not explosive.

Molecular weight: 58 g/mol

Critical temperature: 135 °C

Relative density, liquid: 0,59

Safety data sheet Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 4 / 6

9.2. Other information

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

Unreactive under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May react violently with oxidants., Can form potential explosive atmosphere in air.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Air, Oxidiser. May react violently with alkalis. For material compatibility see latest version of ISO-11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition:
Carbon dioxide, Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

No data available.

Acute inhalation toxicity

Value: LC50

Species: Mouse

Exposure time: 1 h

Value in standard unit mg/l: 52 mg/l

Value: LC50

Species: Rat

Exposure time: 4 h

Value in standard unit mg/l: > 31 mg/l

Acute dermal toxicity

No data available.

Acute toxicity other routes

Ingestion is not considered a potential route of exposure.

Skin irritation

Not classified as an irritant.

Eye irritation

Not classified as an irritant.

Sensitization

No known effects from this product.

Repeated dose toxicity

No data available.

Assessment mutagenicity

There is no evidence of mutagenic potential.

Assessment carcinogenicity

No evidence of carcinogenic effects.

Assessment toxicity to reproduction

No indication of toxic effects.

Assessment teratogenicity

No indication of teratogenic effects.

Experiences with human exposure

Irregular cardiac activity.

Depression of central nervous system.

SECTION 12: Ecological information

12.1. Toxicity

No known ecological damage caused by this product.

Acute and prolonged toxicity fish

Species: Various (Freshwater)

Exposure time: 96 h

Value type: LC50

Value in standard unit mg/l: 27,98 mg/l

Method: Calculated

Acute toxicity aquatic invertebrates

Test type: Fresh water

Species: Daphnia magna

Exposure time: 48 h

Value type: LC50

Value in standard unit mg/l: 16,33 mg/l

Method: Calculated

Toxicity aquatic plants

Test type: Fresh water

Species: Algae

Exposure time: 96 h

Value type: EC50

Value in standard unit mg/l: 8,57 mg/l

Method: Calculated

12.2. Persistence and degradability

Atmospheric degradation

Half life: 6,9 d

12.3. Bioaccumulative potential

Log Pow: 2,7

The substance has no potential for bioaccumulation.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6. Other adverse effects

Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required. Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods.

Safety data sheet Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 5 / 6

Gases in pressure containers (including halons) containing dangerous substances
EWC Nr. 16 05 04*

SECTION 14: Transport information

ADR/RID

14.1. UN number
1969

14.2. UN proper shipping name
Isobutane

14.3. Transport hazard class(es)
Class: 2
Classification Code: 2F
Labels: 2.1
Hazard number: 23
Emergency Action Code: 2YE
Tunnel code: (B/D)

14.4. Packing group (Packing Instruction)
P200

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

IMDG

14.1. UN number
1969

14.2. UN proper shipping name
Isobutane

14.3. Transport hazard class(es)
Class: 2.1
Labels: 2.1
EmS: F-D,S-U

14.4. Packing group (Packing Instruction)
P200

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
Not applicable.

IATA

14.1. UN number
1969

14.2. UN proper shipping name

Isobutane

14.3. Transport hazard class(es)
Class: 2.1
Labels: 2.1

14.4. Packing group (Packing Instruction)
P200

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

Other transport information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the cylinder valve is closed and not leaking. Ensure that the valve outlet cap nut or plug (where provided) is correctly fitted. Ensure that the valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Seveso Directive 96/82/EC: Listed

15.2. Chemical safety assessment
A CSA does not need to be carried out for this product.

SECTION 16: Other information

Ensure all national/local regulations are observed. Ensure operators understand the flammability hazard. Contact with liquid may cause cold burns/frost bite. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Advice

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Details given in this document are believed to be correct at the time of going to press.

Further information

Note:

When using this document care should be taken, as the decimal sign and its position complies with rules for the structure and drafting of international standards, and is a comma on the line.

As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Safety data sheet
Isobutane

Creation date : 28.01.2005
Revision date : 01.06.2011

Version : 1.2

GB / E

SDS No. : 075
page 6 / 6

End of document