

# Safety Data Sheet

Product : **1-Butene** Page :1/4  
MSDS Nr : 302-00-0006BOC(U) Version : 1.02 Date : 03/05/2001  
Replaces version dated : 29/07/1994

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name 1-Butene  
Chemical formula  $\text{CH}_3\text{CH}_2\text{CH}=\text{CH}_2$   
Company identification see heading and/or footer  
Emergency phone numbers see heading and/or footer

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation Substance.  
Components/Impurities Contains no other components or impurities which will influence the classification of the product.  
CAS Nr 00106-98-9  
EC Nr (from EINECS) 203-449-2

## 3 HAZARDS IDENTIFICATION

Hazards identification Liquefied gas  
Extremely flammable

## 4 FIRST AID MEASURES

Inhalation In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.  
In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.  
Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.  
Skin/eye contact In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing.  
Immediately flush eyes thoroughly with water for at least 15 minutes.  
Obtain medical assistance  
Ingestion Ingestion is not considered a potential route of exposure.

## 5 FIRE FIGHTING MEASURES

Specific hazards Exposure to fire may cause containers to rupture/explode.  
Hazardous combustion products Incomplete combustion may form carbon monoxide.  
Suitable extinguishing media All known extinguishants can be used.  
Specific methods If possible, stop flow of product.  
Move away from the container and cool with water from a protected position.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Special protective equipment for fire fighters In confined space use self-contained breathing apparatus.

## 6 ACCIDENTAL RELEASE MEASURES

Personal precautions Evacuate area.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

# Safety Data Sheet

Product :

**1-Butene**

Page :2/4

MSDS Nr : 302-00-0006BOC(U)

Version : 1.02

Date : 03/05/2001

Replaces version dated : 29/07/1994

	be safe.
	Ensure adequate air ventilation.
	Eliminate ignition sources.
Environmental precautions	Try to stop release.
	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Clean up methods	Ventilate area.

## 7 HANDLING AND STORAGE

Handling and storage	Ensure equipment is adequately earthed.
	Suck back of water into the container must be prevented.
	Purge air from system before introducing gas.
	Do not allow backfeed into the container.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
	Keep away from ignition sources (including static discharges).
	Segregate from oxidant gases and other oxidants in store.
	Refer to supplier's container handling instructions.
	Keep container below 50°C in a well ventilated place.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection	Ensure adequate ventilation.
	Do not smoke while handling product.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight	56
Melting point	-185 °C
Boiling point	-6.2 °C
Critical temperature	146 °C
Relative density, gas	1.9 (air=1)
Relative density, liquid	0.63 (water=1)
Vapour Pressure 20°C	2.6 bar
Solubility mg/l water	No reliable data available.
Appearance/Colour	Colourless gas
Odour	Sweetish
	Poor warning properties at low concentrations.
Flammability range	1.6-10 vol% in air.
Autoignition temperature	385 °C
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

# Safety Data Sheet

Product :

**1-Butene**

Page :3/4

MSDS Nr : 302-00-0006BOC(U)

Version : 1.02

Date : 03/05/2001

Replaces version dated : 29/07/1994

## 10 STABILITY AND REACTIVITY

Stability and reactivity

Can form explosive mixture with air.

May react violently with oxidants.

## 11 TOXICOLOGICAL INFORMATION

General

No known toxicological effects from this product.

## 12 ECOLOGICAL INFORMATION

General

No known ecological damage caused by this product.

## 13 DISPOSAL CONSIDERATIONS

General

Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Waste gas should be flared through a suitable burner with flash back arrestor.

Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

## 14 TRANSPORT INFORMATION

UN Nr

1012

Class

2.1

ADR/RID Classification code

2F

ADR/RID Hazard Nr

23

Labelling ADR

Label 2.1: flammable gas

Other transport information

Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers ensure that they are firmly secured and:

- cylinder valve is closed and not leaking
- valve outlet cap nut or plug (where provided) is correctly fitted
- valve protection device (where provided) is correctly fitted
- there is adequate ventilation.
- compliance with applicable regulations.

## 15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548

601-012-00-4.

EC Classification

F+;R12

-Symbols

F+: Extremely flammable

Labelling of cylinders

-Symbols

Label 2.1: flammable gas

-Risk phrases

R12 Extremely flammable.

# Safety Data Sheet

Product :

**1-Butene**

Page :4/4

MSDS Nr : 302-00-0006BOC(U)

Version : 1.02

Date : 03/05/2001

Replaces version dated : 29/07/1994

-Safety phrases

S9 Keep container in well ventilated place.

S16 Keep away from ignition sources - No smoking.

S33 Take precautionary measures against static discharges.

## 16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

Contact with liquid may cause cold burns/frost bite.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Users of breathing apparatus must be trained.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document.****Number of pages :4**